



WL100

Convenient water dispensing unit for budget applications

Economical POU solution for perfectly chilled and hot water

A great value dispenser supplying safe and refreshing drinking water for the workplace without the hassle of bottles. Recommended for up to twenty users, WL100 is the ideal solution for basic hydration needs at a competitive price.

Advanced technology

The WL100 features two core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



BioCote® antimicrobial product protection¹

The key plastic surfaces of the dispenser are integrated with BioCote®, a silver ion additive that prevents microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for crosscontamination.



Waterlogic's promise

Waterlogic combines water science and the latest technologies available to offer safe, great tasting water, whilst preserving the health integrity of the workplace.

¹ Exclusive to Waterlogic in the category for commercial use mains-fed drinking water dispensers and solutions.

Features

Ergonomic design with simple buttons and icons for easy dispensing operation

Touch-less dispensing enabled by foot pedal controls for greater hygiene and piece of mind (optional)

Generous drip tray capacity to collect accidental spillage

BioCote® protected dispensing area

Easy connection to the existing mains water supply

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

345 mm/13.6" (W) x 1030 mm/40.6" (H) x 367 mm/14.4" (D)

Countertop:

345 mm/13.6" (W) x 45 mm/1.8" (H) x 367 mm/14.4" (D)

Dispensing area height

220 mm/8.7"

Weight (Hot and cold models)

Freestanding: 28 kg/~61.7 lb

Countertop: 23 kg/~50.7 lb

Standard filtration supplied

Carbon

Storage capacity

Cold tank: 2 litres (~0.44 US gal)

Hot tank: 1.5 litres (0.4 US gal)

Drip tray capacity

1.5 litres

Compressor

(R600a): 220V-240V/50Hz

(R134a): 110V-120V/60Hz

Water temperatures settings

Cold: 5-8°C/41-46.4°F (default set at 5°C/41°F)

Hot: 85-90°C/185-194°F

Water options

cold sparkling ambient hot extra hot

1				
2				

Number of users: up to 20

Contact the export team today

Waterlogic Trading Ltd
+ 353 1 293 1960
exportsales@waterlogic.com

For more information, visit
www.waterlogic.com

Tested and certified



*certificate may vary depending on different models or products