



# WL100

Convenient water dispensing unit for budget applications

## Economical POU solution for perfectly chilled and hot water

A great value dispenser supplying safe and refreshing drinking water for the workplace without the hassle of bottles. Recommended for up to 20 users, WL100 is the ideal solution for basic hydration needs at a competitive price.

## Advanced technology

The WL100 features two core technologies:



### High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



### BioCote® antimicrobial protection<sup>1</sup>

The key plastic surfaces of the dispenser are integrated with BioCote®, a silver ion additive that prevents microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for crosscontamination.



## Waterlogic's promise

Waterlogic combines water science and the latest technologies available to offer safe, great tasting water, whilst preserving the health integrity of the workplace.



## Features

Ergonomic design with simple buttons and icons for easy dispensing operation

Environmentally friendly refrigeration with R600a: natural occurring refrigerating gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

Generous drip tray capacity to collect accidental spillage

BioCote® protected dispensing area

Easy connection to the existing mains water supply

## Technical specifications

### Types available

Freestanding and countertop

### Dimensions

#### Freestanding:

345mm (W) x 1030mm (H) x 367mm (D)

#### Countertop:

345mm (W) x 457mm (H) x 367mm (D)

### Dispensing area height

220 mm

### Weight (Hot and cold models)

Freestanding: 28 kg

Countertop: 23 kg

### Standard filtration supplied

Carbon

### Storage capacity

Cold tank: 2 litres

Hot tank: 1.5 litres

### Drip tray capacity

1.5 litres

### Compressor

220/240v 50Hz (R600a)




### Water temperatures settings

Cold: 5-8°C (default set at 5°C)

Hot: 85-90°C

## Water options

cold    sparkling    ambient    hot    extra hot

1				
2				

## Number of users 10-20

## Contact us today

United Kingdom

[www.waterlogic.co.uk](http://www.waterlogic.co.uk)

+44 (0) 333 323 2307

[info@waterlogic.co.uk](mailto:info@waterlogic.co.uk)

Ireland

[www.waterlogic.ie](http://www.waterlogic.ie)

+353 1466 0133

[info@waterlogic.ie](mailto:info@waterlogic.ie)

## Tested and certified



\*certificate may vary depending on different models or products